



# TRITON

## OUR SECTORS

### Agricultural

Triton Containers are supplied in clean IICL-6 condition and can be used for storage at origin or destination.



## OUR SECTORS – AGRICULTURAL

# Equipment that is built to last

We provide a safety net of equipment and additional operational flexibility ideal for the agriculture sector.

Triton Containers are supplied in a range of conditions subject to your needs, and can be used for cost-effective storage at origin or destination.

### Weather and vermin resistant mobile containers

Triton Dry and Refrigerated Containers provide companies operating within the agriculture sector with an economical solution for securely storing equipment and critical supplies such as animal feed, agricultural grain, stock, fertilizers, pesticides, and machinery.

Alongside an array of tailored leasing options, we also sell containers in various colors and conditions globally. Triton used “Cargoworthy” units are ideal for securing valuable equipment and stock on-site. Alternatively, our “As-Is” condition units vary in quality but are typically suitable for field use.

We can also supply agricultural shippers with Shipper Owned Containers for international one-way use.

### Triton Tank Containers

ISO Tank Containers have long been the go-to equipment type for safely transporting bulk liquid agricultural products around the globe. When used to transport cargo intermodally, they are more economical and produce less CO2 emissions than other methods. They are available globally with four different capacities, including 21000 liters, 25,000 liters, 26,000 liters, and 35,000 liters.

**PLEASE NOTE:** The following pages showcase a small sample of products in the Triton global inventory. We stock a wide range of products for lease and sale in various conditions. Get in touch with your local Triton representative for more information.



# 10ft Dry Container



## CLASSIFICATION


### For Sale: New

Available via Triton's global network of supply locations.



## FEATURES

- Manufactured with rust resistant corten steel
- Secure and weatherproof, with vents to allow airflow
- Superior paint systems
- Incredibly versatile and suitable for customers to modify into a wide range of applications
- Advance orders in your preferred color (minimum volume required)
- Ideal for smaller domestic applications such as the construction industry
- Great options including 80 micron floor coating, lock boxes, waist high door locking handles
- Triton's industry leading new production testing and inspection criteria ensures the highest quality container
- Shipping costs can be minimized by loading 2x10' units joined together (using approved ISO certification method)
- Moved from factory to most major ports in the world
- Backed up by Triton's global network of supply locations and dedicated sales and support teams
- Available globally



## DIMENSIONS (METRIC/IMPERIAL)

### EXTERNAL DIMENSIONS

<b>Length</b>	2,991 mm	9' 9.8"
<b>Width</b>	2,438 mm	8' 0.0"
<b>Height</b>	2,591 mm	8' 6.0"

### INTERNAL DIMENSIONS

<b>Length</b>	2,831 mm	9' 3.5"
<b>Width</b>	2,352 mm	7' 8.6"
<b>Height</b>	2,393 mm	7' 10.2"

### DOOR OPENING

<b>Width</b>	2,338 mm	7' 8.0"
<b>Height</b>	2,280 mm	7' 5.8"

### CAPACITY & WEIGHTS

<b>Inside Cubic Capacity</b>	15.9 m <sup>3</sup>	563 ft <sup>3</sup>
<b>Max Gross</b>	10,160 kg	22,400 lbs
<b>Payload</b>	8,960 kg	19,755 lbs
<b>Tare</b>	1,200 kg	2,645 lbs

**NOTE:** The dimensions and door openings of all containers correspond to ISO standards. However, due to production tolerances, a difference in measurement is possible.

**DISCLAIMER:** Every effort is made to ensure this information is accurate, however Triton does not assume any liability for the accuracy of the information and content provided in marketing or information materials, or for the consequences resulting from using the information and content provided. Triton does not guarantee or claim that said information and content is exhaustive. Claims as to the exhaustive nature of said information and content are excluded. The information and content is only provided for advertising purposes and is non-binding. No explicit or implied warranties or guarantees are made. The container displayed only represents a sample of the entire fleet.

The following items are registered or unregistered service marks in the United States and/or foreign jurisdictions pursuant to applicable intellectual property law and are the property of Triton International Limited and its subsidiaries: Triton® and TAL®.



## 20ft Dry Container



### CLASSIFICATION

#### Lease


Available via Triton's global network of supply locations.



### FEATURES

- Manufactured with rust resistant corten steel
- Secure and weatherproof, with vents to allow airflow
- Resistant to damage and corrosion
- Superior paint systems
- Triton's industry leading new production testing and inspection criteria ensures the highest quality container
- Incredibly versatile
- Backed up by Triton's global network of supply locations and dedicated leasing and support teams
- Available globally
- IICL-6 repair criteria saves cost at off-hire
- Damage Protection Plan available to reduce costs and time at off-hire
- Flexible lease terms to meet your company needs





DIMENSIONS (METRIC/IMPERIAL)

EXTERNAL DIMENSIONS

Length	6,058 mm	19' 10.5"
Width	2,438 mm	8' 0.0"
Height	2,591 mm	8' 6.0"

INTERNAL DIMENSIONS

Length	5,898 mm	19' 4.2"
Width	2,352 mm	7' 8.6"
Height	2,393 mm	7' 10.2"

DOOR OPENING

Width	2,340 mm	7' 8.1"
Height	2,280 mm	7' 5.8"

CAPACITY & WEIGHTS


Inside Cubic Capacity	33.2 m <sup>3</sup>	1172 ft <sup>3</sup>
Max Gross	30,480 kg	67,200 lbs
Payload	28,380 kg	62,570 lbs
Tare	2,100 kg	4,630 lbs

**NOTE:** The dimensions and door openings of all containers correspond to ISO standards. However, due to production tolerances, a difference in measurement is possible.

**DISCLAIMER:** Every effort is made to ensure this information is accurate, however Triton does not assume any liability for the accuracy of the information and content provided in marketing or information materials, or for the consequences resulting from using the information and content provided. Triton does not guarantee or claim that said information and content is exhaustive. Claims as to the exhaustive nature of said information and content are excluded. The information and content is only provided for advertising purposes and is non-binding. No explicit or implied warranties or guarantees are made. The container displayed only represents a sample of the entire fleet.

The following items are registered or unregistered service marks in the United States and/or foreign jurisdictions pursuant to applicable intellectual property law and are the property of Triton International Limited and its subsidiaries: Triton® and TAL®.




  
**CLASSIFICATION**  
**Lease**  
Available via Triton's  
global network of supply  
locations.

# 20ft Refrigerated Container



## FEATURES

- Designed for safe transportation of temperature sensitive cargo and frozen & perishable goods. (Food-grade approved)
- Ideal for on-site temperature controlled storage
- Strong, robust, insulated and repair friendly
- State-of-the art design and low power consumption makes units highly efficient
- Standard features: HGSS roof end panels, T-bar flooring and interior aluminum scuff lining
- Triton's industry leading new production testing and inspection criteria ensures the highest quality container
- Can be ordered with Carrier, Starcool, Daikin or Thermo King machinery, with 3 Phase Power. These leading brands offer worldwide availability for parts and service
- Provisioned for track & trace feature
- Resistant to bacteria
- Low heat leakage values
- Low GWP refrigerants compatible
- Backed up by Triton's global network of supply locations and dedicated leasing and support teams
- Available globally



## DIMENSIONS (METRIC/IMPERIAL)

### EXTERNAL DIMENSIONS

<b>Length</b>	6,058 mm	19' 10.5"
<b>Width</b>	2,438 mm	8' 0.0"
<b>Height</b>	2,591 mm	8' 6.0"

### INTERNAL DIMENSIONS

<b>Length</b>	5,454 mm	17' 10.7"
<b>Width</b>	2,290 mm	7' 6.2"
<b>Height</b>	2,276 mm	7' 5.6"

### DOOR OPENING

<b>Width</b>	2,294 mm	7' 6.3"
<b>Height</b>	2,264 mm	7' 5.1"

### CAPACITY & WEIGHTS

<b>Inside Cubic Capacity</b>	28.4 m <sup>3</sup>	1003 ft <sup>3</sup>
<b>Max Gross</b>	30,480 kg	67,200 lbs
<b>Payload</b>	27,650 kg	60,960 lbs
<b>Tare*</b>	2,830 kg	6,240 lbs

\*Tare can vary slightly based on reefer machine type.

**NOTE:** The dimensions and door openings of all containers correspond to ISO standards. However, due to production tolerances, a difference in measurement is possible.

**DISCLAIMER:** Every effort is made to ensure this information is accurate, however Triton does not assume any liability for the accuracy of the information and content provided in marketing or information materials, or for the consequences resulting from using the information and content provided. Triton does not guarantee or claim that said information and content is exhaustive. Claims as to the exhaustive nature of said information and content are excluded. The information and content is only provided for advertising purposes and is non-binding. No explicit or implied warranties or guarantees are made. The container displayed only represents a sample of the entire fleet.

The following items are registered or unregistered service marks in the United States and/or foreign jurisdictions pursuant to applicable intellectual property law and are the property of Triton International Limited and its subsidiaries: Triton® and TAL®.





## CLASSIFICATION

### Lease


Available via Triton's global network of supply locations.

# 40ft High Cube Refrigerated Container



## FEATURES

- Additional height provides extra internal cubic capacity, which means greater interior stacking capacity for your goods
- Designed for safe transportation of temperature sensitive cargo and frozen and perishable goods. (Food-grade approved)
- Ideal for on-site temperature controlled storage
- Strong, robust, insulated and repair friendly
- State-of-the-art design and low power consumption makes units highly efficient
- Standard features: HGSS roof end panels, T-bar flooring and interior aluminum scuff lining
- Provisioned for track & trace feature
- Triton's industry leading new production testing and inspection criteria ensures the highest quality container
- Resistant to bacteria
- Low heat leakage values
- Low GWP refrigerants compatible
- Can be ordered with Carrier, Starcool, Daikin or Thermo King machinery, with 3 Phase Power. These leading brands offer worldwide availability for parts and service
- Backed up by Triton's global network of supply locations and dedicated leasing and support teams
- Available globally



DIMENSIONS (METRIC/IMPERIAL)

EXTERNAL DIMENSIONS

Length	12,192 mm	40' 0.0"
Width	2,438 mm	8' 0.0"
Height	2,896 mm	9' 6.0"

INTERNAL DIMENSIONS

Length	11,588 mm	38' 0.2"
Width	2,290 mm	7' 6.2"
Height	2,547.5 mm	8' 4.3"

DOOR OPENING

Width	2,294 mm	7' 6.3"
Height	2,569 mm	8' 5.1"

CAPACITY & WEIGHTS

Inside Cubic Capacity	67.6 m <sup>3</sup>	2,387 ft <sup>3</sup>
Max Gross	35,000 kg	77,160 lbs
Payload	30,440 kg	67,110 lbs
Tare*	4,560 kg	10,050 lbs

\*Tare can vary slightly based on reefer machine type.

**NOTE:** The dimensions and door openings of all containers correspond to ISO standards. However, due to production tolerances, a difference in measurement is possible.

**DISCLAIMER:** Every effort is made to ensure this information is accurate, however Triton does not assume any liability for the accuracy of the information and content provided in marketing or information materials, or for the consequences resulting from using the information and content provided. Triton does not guarantee or claim that said information and content is exhaustive. Claims as to the exhaustive nature of said information and content are excluded. The information and content is only provided for advertising purposes and is non-binding. No explicit or implied warranties or guarantees are made. The container displayed only represents a sample of the entire fleet.

The following items are registered or unregistered service marks in the United States and/or foreign jurisdictions pursuant to applicable intellectual property law and are the property of Triton International Limited and its subsidiaries: Triton® and TAL®.



# 45ft Used High Cube Pallet Wide Refrigerated Container



## CLASSIFICATION


### For Sale: Used

Available via Triton's global network of supply locations.



## FEATURES

- Available in a range of conditions to suit all needs
- Additional height and length provides extra internal cubic capacity, which means greater interior stacking capacity for your goods
- Refrigerated and insulated shipping containers
- Designed for safe transportation of perishable food, beverages and temperature sensitive cargo
- Ideal for on-site temperature controlled storage
- State of the art design makes units highly efficient
- Most units have stainless steel lined interiors and T-bar flooring
- Most machinery comes with 3 Phase power and CFC friendly refrigerant
- Backed up by Triton's global network of supply locations and dedicated sales and support teams
- Available globally



DIMENSIONS (METRIC/IMPERIAL)

EXTERNAL DIMENSIONS

Length	13,813 mm	45' 0.0"
Width	2,550 mm	8' 3.6"
Height	2,900 mm	9' 5.1"

INTERNAL DIMENSIONS

Length	13,261 mm	43' 0.0"
Width	2,440 mm	8' 0.0"
Height	2,570 mm	8' 4.3"

DOOR OPENING

Width	2,440 mm	8' 0.0"
Height	2,570 mm	8' 4.3"

CAPACITY & WEIGHTS

Inside Cubic Capacity	83.5 m <sup>3</sup>	2,949 ft <sup>3</sup>
Max Gross	35,000 kg	77,160 lbs
Payload	28,920 kg	63,760 lbs
Tare*	6,080 kg	13,400 lbs

\*Tare can vary slightly based on reefer machine type.

**NOTE:** The dimensions and door openings of all containers correspond to ISO standards. However, due to production tolerances, a difference in measurement is possible.

**DISCLAIMER:** Every effort is made to ensure this information is accurate, however Triton does not assume any liability for the accuracy of the information and content provided in marketing or information materials, or for the consequences resulting from using the information and content provided. Triton does not guarantee or claim that said information and content is exhaustive. Claims as to the exhaustive nature of said information and content are excluded. The information and content is only provided for advertising purposes and is non-binding. No explicit or implied warranties or guarantees are made. The container displayed only represents a sample of the entire fleet. The following items are registered or unregistered service marks in the United States and/or foreign jurisdictions pursuant to applicable intellectual property law and are the property of Triton International Limited and its subsidiaries: Triton® and TAL®.





# 20ft Flush Folding Flatracks



## CLASSIFICATION

### Lease



Available via Triton's global network of supply locations.



## FEATURES

- Built to carry heavy or oversized cargoes
- Great for specialized shipments of steel, pipes, drums and machinery
- Forklift pockets for easy empty handling
- Heavy duty steel frames and thick plank floors and lashing rings all around
- With flush folding end frames to allow for efficient stacking and repositioning
- Triton's industry leading new production testing and inspection criteria ensures the highest quality container
- Available in the high demand hub ports
- Backed up by Triton's global network of supply locations and dedicated leasing and support teams
- Flexible lease terms to meet your company needs





## DIMENSIONS (METRIC/IMPERIAL)

### EXTERNAL DIMENSIONS

<b>Length</b> (Base bottom casting)	6,058 mm	19' 10.5"
<b>Width</b> (Base bottom casting)	2,438 mm	8' 0.0"
<b>Height</b> (End frame up)	2,591 mm	8' 6.0"
<b>Height</b> (End frame down)	370 mm	1' 2.6"

### INTERNAL DIMENSIONS

<b>Length</b> (Between end panels)	6,038 mm	19' 9.7"
<b>Width</b> (Over bottom side rail)	2,194 mm	7' 2.4"
<b>Height</b> (Side rail to top castings)	2,233 mm	7' 3.9"

### CAPACITY & WEIGHTS

<b>Max Gross</b>	45,000 kg	99,200 lbs
<b>Payload</b>	42,000 kg	92,590 lbs
<b>Tare</b>	3,000 kg	6,640 lbs

**NOTE:** The dimensions of containers correspond to ISO standards.

However, due to production tolerances, a difference in measurement is possible.

**DISCLAIMER:** Every effort is made to ensure this information is accurate, however Triton does not assume any liability for the accuracy of the information and content provided in marketing or information materials, or for the consequences resulting from using the information and content provided. Triton does not guarantee or claim that said information and content is exhaustive. Claims as to the exhaustive nature of said information and content are excluded. The information and content is only provided for advertising purposes and is non-binding. No explicit or implied warranties or guarantees are made. The container displayed only represents a sample of the entire fleet.

The following items are registered or unregistered service marks in the United States and/or foreign jurisdictions pursuant to applicable intellectual property law and are the property of Triton International Limited and its subsidiaries: Triton® and TAL®.



## CLASSIFICATION

### Lease


Available via Triton's global network of supply locations.

# 40ft Flush Folding Flatracks



## FEATURES

- Built to carry heavy or oversized cargoes
- Great for specialized shipments of steel, pipes, drums and machinery
- Forklift pockets for easy empty handling
- Heavy duty steel frames and thick plank floors and lashing rings all around
- With flush folding end frames to allow for efficient stacking and repositioning
- Triton's industry leading new production testing and inspection criteria ensures the highest quality container
- Available in the high demand hub ports
- Backed up by Triton's global network of supply locations and dedicated leasing and support teams
- Flexible lease terms to meet your company needs



## DIMENSIONS (METRIC/IMPERIAL)

### EXTERNAL DIMENSIONS

<b>Length</b> (Base bottom casting)	12,192 mm	40' 0.0"
<b>Width</b> (Base bottom casting)	2,438 mm	8' 0.0"
<b>Height</b> (End frame up)	2,591 mm	8' 6.0"
<b>Height</b> (End frame down)	648 mm	2' 1.5"

### INTERNAL DIMENSIONS

<b>Length</b> (Between end panels)	12,182 mm	39' 11.6"
<b>Width</b> (Over bottom side rail)	2,374 mm	7' 9.5"
<b>Height</b> (Side rail to top castings)	1,959 mm	6' 5.1"

### CAPACITY & WEIGHTS

<b>Max Gross</b>	52,500 kg	115,740 lbs
<b>Payload</b>	47,260 kg	104,190 lbs
<b>Tare</b>	5,240 kg	11,550 lbs

**NOTE:** The dimensions of containers correspond to ISO standards.

However, due to production tolerances, a difference in measurement is possible.

**DISCLAIMER:** Every effort is made to ensure this information is accurate, however Triton does not assume any liability for the accuracy of the information and content provided in marketing or information materials, or for the consequences resulting from using the information and content provided. Triton does not guarantee or claim that said information and content is exhaustive. Claims as to the exhaustive nature of said information and content are excluded. The information and content is only provided for advertising purposes and is non-binding. No explicit or implied warranties or guarantees are made. The container displayed only represents a sample of the entire fleet.

The following items are registered or unregistered service marks in the United States and/or foreign jurisdictions pursuant to applicable intellectual property law and are the property of Triton International Limited and its subsidiaries: Triton® and TAL®.



## CLASSIFICATION

### Lease


Available via Triton's global network of supply locations.

# 40ft High Cube Flush Folding Flatracks



## FEATURES

- Additional height provides extra capacity for your goods
- Built to carry heavy or out of gauge cargoes
- Heavy duty steel frames and thick plank floors
- Great for specialized shipments of steel, pipes, drums and machinery
- With flush folding end frames to allow for efficient stacking
- Triton's industry leading new production testing and inspection criteria ensures the highest quality container
- Backed up by Triton's global network of supply locations and dedicated leasing and support teams
- Flexible lease terms to meet your company needs



## DIMENSIONS (METRIC/IMPERIAL)

### EXTERNAL DIMENSIONS

<b>Length</b> (Base bottom casting)	12,192 mm	40' 0.0"
<b>Width</b> (Base bottom casting)	2,438 mm	8' 0.0"
<b>Height</b> (End frame up)	2,896 mm	9' 6.0"
<b>Height</b> (End frame down)	648 mm	2' 1.5"

### INTERNAL DIMENSIONS

<b>Length</b> (Between end panels)	12,182 mm	39' 11.6"
<b>Width</b> (Over bottom side rail)	2,374 mm	7' 9.5"
<b>Height</b> (Side rail to top castings)	2,264 mm	7' 5.1"

### CAPACITY & WEIGHTS

<b>Max Gross</b>	52,500 kg	115,740 lbs
<b>Payload</b>	47,220 kg	104,100 lbs
<b>Tare</b>	5,280 kg	11,640 lbs

**NOTE:** The dimensions of containers correspond to ISO standards. However, due to production tolerances, a difference in measurement is possible.

**DISCLAIMER:** Every effort is made to ensure this information is accurate, however Triton does not assume any liability for the accuracy of the information and content provided in marketing or information materials, or for the consequences resulting from using the information and content provided. Triton does not guarantee or claim that said information and content is exhaustive. Claims as to the exhaustive nature of said information and content are excluded. The information and content is only provided for advertising purposes and is non-binding. No explicit or implied warranties or guarantees are made. The container displayed only represents a sample of the entire fleet.

The following items are registered or unregistered service marks in the United States and/or foreign jurisdictions pursuant to applicable intellectual property law and are the property of Triton International Limited and its subsidiaries: Triton® and TAL®.





# 20ft Used Flush Folding Flatracks



## CLASSIFICATION


### For Sale: Used

Available via Triton's global network of supply locations.



## FEATURES

- Built to carry heavy or out of gauge cargoes
- Great for specialized shipments of coiled steel, drums and machinery
- Heavy duty steel frames and thick plank floors
- Many with flush folding end frames to allow for efficient stacking
- Backed up by Triton's global network of supply locations and dedicated sales and support teams
- Available globally



## DIMENSIONS (METRIC/IMPERIAL)

### EXTERNAL DIMENSIONS

<b>Length</b> (Base bottom casting)	6,058 mm	19' 10.5"
<b>Width</b> (Base bottom casting)	2,438 mm	8' 0.0"
<b>Height</b> (End frame up)	2,591 mm	8' 6.0"
<b>Height</b> (End frame down)	370 mm	1' 2.6"

### INTERNAL DIMENSIONS

<b>Length</b> (Between end panels)	6,038 mm	19' 9.7"
<b>Width</b> (Over bottom side rail)	2,194 mm	7' 2.4"
<b>Height</b> (Side rail to top castings)	2,233 mm	7' 3.9"

**NOTE:** The dimensions of containers correspond to ISO standards.  
However, due to production tolerances, a difference in measurement is possible.

**DISCLAIMER:** Every effort is made to ensure this information is accurate, however Triton does not assume any liability for the accuracy of the information and content provided in marketing or information materials, or for the consequences resulting from using the information and content provided. Triton does not guarantee or claim that said information and content is exhaustive. Claims as to the exhaustive nature of said information and content are excluded. The information and content is only provided for advertising purposes and is non-binding. No explicit or implied warranties or guarantees are made. The container displayed only represents a sample of the entire fleet.

The following items are registered or unregistered service marks in the United States and/or foreign jurisdictions pursuant to applicable intellectual property law and are the property of Triton International Limited and its subsidiaries: Triton® and TAL®.

### CAPACITY & WEIGHTS

<b>Max Gross</b>	34,000 kg	74,960 lbs
<b>Payload</b>	31,110 – 31,350 kg	65,150 – 65,570 lbs
<b>Tare</b>	2,650 – 2,890 kg	9,390 – 9,810 lbs



#### CLASSIFICATION

#### For Sale: Used


Available via Triton's global network of supply locations.

## 40ft Used Flush Folding Flatracks



#### FEATURES

- Built to carry heavy or out of gauge cargoes
- Heavy duty steel frames and thick plank floors
- Backed up by Triton's global network of supply locations and dedicated sales and support teams
- Great for specialized shipments of coiled steel, drums and machinery
- Many with flush folding end frames to allow for efficient stacking
- Available globally



## DIMENSIONS (METRIC/IMPERIAL)

### EXTERNAL DIMENSIONS

<b>Length</b> (Base bottom casting)	12,192 mm	40' 0.0"
<b>Width</b> (Base bottom casting)	2,438 mm	8' 0.0"
<b>Height</b> (End frame up)	2,591 mm	8' 6.0"
<b>Height</b> (End frame down)	648 mm	2' 1.5"

### INTERNAL DIMENSIONS

<b>Length</b> (Between end panels)	12,182 mm	39' 11.6"
<b>Width</b> (Over bottom side rail)	2,374 mm	7' 9.5"
<b>Height</b> (Side rail to top castings)	1,959 mm	6' 5.1"

### CAPACITY & WEIGHTS

<b>Max Gross</b>	45,000, 50,000 or 52,500kg 99,210, 110,230 or 115,740 lbs
<b>Payload</b>	39,200 – 47,520kg 86,421 – 104,764 lbs
<b>Tare</b>	4,780 kg – 5,800 kg 10,538 lbs – 12,787 lbs

**NOTE:** The dimensions of containers correspond to ISO standards.  
However, due to production tolerances, a difference in measurement is possible.

**DISCLAIMER:** Every effort is made to ensure this information is accurate, however Triton does not assume any liability for the accuracy of the information and content provided in marketing or information materials, or for the consequences resulting from using the information and content provided. Triton does not guarantee or claim that said information and content is exhaustive. Claims as to the exhaustive nature of said information and content are excluded. The information and content is only provided for advertising purposes and is non-binding. No explicit or implied warranties or guarantees are made. The container displayed only represents a sample of the entire fleet.

The following items are registered or unregistered service marks in the United States and/or foreign jurisdictions pursuant to applicable intellectual property law and are the property of Triton International Limited and its subsidiaries: Triton® and TAL®.



# 40ft Used High Cube Flush Folding Flatracks



## CLASSIFICATION

### For Sale: Used

Available via Triton's global network of supply locations.

## FEATURES

- Additional height provides extra capacity for your goods
- Built to carry heavy or out of gauge cargoes
- Great for specialized shipments of coiled steel, drums and machinery
- Heavy duty steel frames and thick plank floors
- Many with flush folding end frames to allow for efficient stacking
- Backed up by Triton's global network of supply locations and dedicated sales and support teams
- Available globally





## DIMENSIONS (METRIC/IMPERIAL)

### EXTERNAL DIMENSIONS

<b>Length</b> (Base bottom casting)	12,192 mm	40' 0.0"
<b>Width</b> (Base bottom casting)	2,438 mm	8' 0.0"
<b>Height</b> (End frame up)	2,896 mm	9' 6.0"
<b>Height</b> (End frame down)	648 mm	2' 1.5"

### INTERNAL DIMENSIONS

<b>Length</b> (Between end panels)	12,182 mm	39' 11.6"
<b>Width</b> (Over bottom side rail)	2,374 mm	7' 9.5"
<b>Height</b> (Side rail to top castings)	2,264 mm	7' 5.1"

### CAPACITY & WEIGHTS

<b>Max Gross</b>	45,000 – 50,000 kg 99,210 – 110,230 lbs
<b>Payload</b>	39,300 – 47,200 kg 86,640 – 104,060 lbs
<b>Tare</b>	5,300 kg – 5,950 kg 11,680 lbs – 13,120 lbs

**NOTE:** The dimensions of containers correspond to ISO standards. However, due to production tolerances, a difference in measurement is possible.

**DISCLAIMER:** Every effort is made to ensure this information is accurate, however Triton does not assume any liability for the accuracy of the information and content provided in marketing or information materials, or for the consequences resulting from using the information and content provided. Triton does not guarantee or claim that said information and content is exhaustive. Claims as to the exhaustive nature of said information and content are excluded. The information and content is only provided for advertising purposes and is non-binding. No explicit or implied warranties or guarantees are made. The container displayed only represents a sample of the entire fleet.

The following items are registered or unregistered service marks in the United States and/or foreign jurisdictions pursuant to applicable intellectual property law and are the property of Triton International Limited and its subsidiaries: Triton® and TAL®.



# ISO Fluid Tank Container



## CLASSIFICATION


### Lease

Available via Triton's global network of supply locations.



## FEATURES

- UN portable tank: Type T11 and T14 available
- Capacities ranging from 21000l to 35000l
- Approved for ADR/RID/IMDG transportation
- Suitable for the carriage of most bulk liquids
- General specs include a high quality stainless steel tank barrel
- Full frame type design with B-style walkway
- Internationally recognized fittings
- Insulation with steam heating capability
- Rigorous quality control of our 3rd party production facilities
- Backed up by Triton's global network of supply locations and dedicated leasing and support teams
- Available globally
- Flexible lease terms to meet your company needs



### DIMENSIONS (METRIC/IMPERIAL)

#### FRAME DIMENSIONS (20' Equivalent)

Length	6,058 mm	19' 10.5"
Width	2,438 mm	8' 0.0"
Height	2,591 mm	8' 6.0"

#### WEIGHT, PRESSURE & TEMPERATURE

Maximum Gross Weight	36,000 kg
Tare Weight	3,710 kg
Payload	32,290 kg
Maximum Allowable Working Pressure	4.00 bar
Design Temperature (frame & tank)	-40°C to +130°C

**NOTE:** The dimensions and door openings of all containers correspond to ISO standards. However, due to production tolerances, a difference in measurement is possible.

**DISCLAIMER:** Every effort is made to ensure this information is accurate, however Triton does not assume any liability for the accuracy of the information and content provided in marketing or information materials, or for the consequences resulting from using the information and content provided. Triton does not guarantee or claim that said information and content is exhaustive. Claims as to the exhaustive nature of said information and content are excluded. The information and content is only provided for advertising purposes and is non-binding. No explicit or implied warranties or guarantees are made. The container displayed only represents a sample of the entire fleet. The following items are registered or unregistered service marks in the United States and/or foreign jurisdictions pursuant to applicable intellectual property law and are the property of Triton International Limited and its subsidiaries: Triton® and TAL®.

### OPTIONS

#### AVAILABLE ISO TANKS T11 TYPES

20ft	21,000 litre
20ft	25,000 litre
20ft	26,000 litre

#### AVAILABLE NON-ISO T11 TYPES

7.82m Swap Body	35,000 litre
-----------------	--------------



#### CLASSIFICATION

#### For Sale: Used

Available via Triton's global network of supply locations.


# Used ISO Fluid Tank Container



## FEATURES

- UN Portable Tank: Type T11 and T14
- Capacities ranging from 21000l to 35000l
- Approved for ADR/RID/IMDG transportation
- Suitable for the carriage of most bulk liquids
- General specs include a high quality stainless steel tank barrel
- Full frame type design with B-style walkway
- Internationally recognized fittings
- Insulation with steam heating capability
- Rigorous quality control of our 3rd party production facilities
- Backed up by Triton's global network of supply locations and dedicated sales and support teams
- Available globally in all hub locations





### DIMENSIONS (METRIC/IMPERIAL)

#### FRAME DIMENSIONS (20' Equivalent)

Length	6,058 mm	19' 10.5"
Width	2,438 mm	8' 0.0"
Height	2,591 mm	8' 6.0"

#### WEIGHT, PRESSURE & TEMPERATURE

Maximum Gross Weight	36,000 kg
Tare Weight	3,500–3,910 kg
Payload	32,090–32,500 kg
Maximum Allowable Working Pressure	4.00 bar
Design Temperature (frame & tank)	–40°C to +130°C

**NOTE:** The dimensions and door openings of all containers correspond to ISO standards. However, due to production tolerances, a difference in measurement is possible.

**DISCLAIMER:** Every effort is made to ensure this information is accurate, however Triton does not assume any liability for the accuracy of the information and content provided in marketing or information materials, or for the consequences resulting from using the information and content provided. Triton does not guarantee or claim that said information and content is exhaustive. Claims as to the exhaustive nature of said information and content are excluded. The information and content is only provided for advertising purposes and is non-binding. No explicit or implied warranties or guarantees are made. The container displayed only represents a sample of the entire fleet. The following items are registered or unregistered service marks in the United States and/or foreign jurisdictions pursuant to applicable intellectual property law and are the property of Triton International Limited and its subsidiaries: Triton® and TAL®.

### OPTIONS

#### AVAILABLE ISO TANKS T11 TYPES

20ft	21,000 litre
20ft	25,000 litre
20ft	26,000 litre

#### AVAILABLE NON-ISO T11 TYPES

7.82m Swap Body	35,000 litre
-----------------	--------------



HERE. THERE. EVERYWHERE

# We supply the world

Triton is the largest lessor of intermodal containers in the world with over 7 million TEU of containers. Our services are available in 89 countries around the globe. So, no matter where you need containers, we'll have them nearby. To find your nearest Triton Container Sales manager visit [www.tritoncontainer.com](http://www.tritoncontainer.com).



**Global inventory of  
cargoworthy containers  
for lease and sale.**



**Unrivalled container  
supply at competitive  
prices.**



**Outstanding and  
highly responsive  
customer services.**



**Global network of 20 offices  
and 3 independent agencies  
across 16 countries.**



**Equipment  
built to the  
highest quality.**



**Our size, strength and reliability  
make us the go-to supplier of  
intermodal shipping containers.**



We're the biggest for a reason, contact our friendly experts and experience Triton's world-leading service and cost savings today. Imagine what we can do together.

[www.tritoncontainer.com](http://www.tritoncontainer.com)