

OUR SECTORS

Machinery

Our global inventory includes specialist equipment specifically designed to transport heavy and oversized machinery.



OUR SECTORS - MACHINERY

Specialist equipment for challenging cargo

We are the world's largest lessor of intermodal containers and equipment, including Flatracks, Open Top Containers, and Dry Containers. Our products are frequently utilized by manufacturing and transportation businesses that operate worldwide.

Flatrack Containers

With a higher load capacity than standard Dry Containers of the same size, Flatracks are predominantly used to transport heavy, oversized cargo. Easily accessible from the side and above, they are built to accommodate industrial machinery that cannot be loaded into a standard container.

Open Top Containers

Triton Open Top Containers are supplied with weather-resistant tarpaulin roofs to protect cargo from the elements. The removable, flexible covers and swingable/removable door headers, enable items to be loaded from above using a crane or rolling bridge, allowing businesses to safely ship specialist loads, including oversized machinery.

PLEASE NOTE: The following pages showcase a small sample of products in the Triton global inventory. We stock a wide range of products for lease and sale in various conditions. Get in touch with your local Triton representative for more information.





Lease

Available via Triton's global network of supply locations.


20ft **Open Top** Container




- · Corrugated steel panels with strong wooden floor to protect the cargo
- Designed for cargos that require special loading dimensions
- · Removable door header

- · Removable roof bows and durable tarpaulin with customs approved cable to cover the topside
- · Two swingable doors with custom approved closures
- 11/8" thick marine wooden floors with center dividers

- · Several lashing rings and bars inside the container to secure the cargo
- · Forklift pockets for easy empty handling
- · Triton's industry leading new production testing and inspection criteria ensures the highest quality container
- · Backed up by Triton's global network of supply locations and dedicated leasing and support teams
- · Available in the high demand hub ports
- Flexible lease terms to meet your company needs





EXTERNAL DIMENSIONS

Length	6,058 mm	19′ 10.5″
Width	2,438 mm	8′ 0.0″
Height	2,591 mm	8′ 6.0″

INTERNAL DIMENSIONS

Length	5,895 mm	19′ 4.2
Width (Between side panels)	2,352 mm	7′ 8.6
Height	2,348 mm	7′ 8.4

DOOR OPENING

Width	2,340 mm	7′ 8.1″
Height	2,280 mm	7′ 5.8″

CAPACITY & WEIGHTS

Inside Cubic Cap	acity 32.5 m³	1,150 ft°
Max Gross	30,480 kg	67,200 lbs
Payload	28,320 kg	62,440 lbs
Tare	2,160 kg	4,760 lbs

NOTE: The dimensions and door openings of all containers correspond to ISO standards. However, due to production tolerances, a difference in measurement is possible.

DISCLAIMER: Every effort is made to ensure this information is accurate, however Triton does not assume any liability for the accuracy of the information and content provided in marketing or information materials, or for the consequences resulting from using the information and content provided. Triton does not guarantee or claim that said information and content is exhaustive. Claims as to the exhaustive nature of said information and content are excluded. The information and content is only provided for advertising purposes and is non-binding. No explicit or implied warranties or guarantees are made. The container displayed only represents a sample of the entire fleet.





Lease

Available via Triton's global network of supply locations.

40ft **Open Top** Container




- · Corrugated steel panels with strong wooden floor to protect the cargo
- Designed for cargos that require special loading dimensions
- · Removable door header

- · Removable roof bows and durable tarpaulin with customs approved cable to cover the topside.
- · Two swingable doors with custom approved closures
- 11/8" thick marine wooden floors with center dividers

- · Several lashing rings and bars inside the container to secure the cargo
- · Triton's industry leading new production testing and inspection criteria ensures the highest quality container
- Backed up by Triton's global network of supply locations and dedicated leasing and support teams
- · Available in the high demand hub ports
- · Flexible lease terms to meet your company needs





EXTERNAL DIMENSIONS

Length	12,192 mm	40′ 0.0″
Width	2,438 mm	8′ 0.0″
Height	2,591 mm	8′ 6.0″

INTERNAL DIMENSIONS

Length	12,032 mm	39′ 5.7′
Width	2,352 mm	7′ 8.6′
Height	2,348 mm	7′ 8.4′

DOOR OPENING

Width	2,340 mm	7′ 8.1′
Height	2,280 mm	7′ 5.8′

CAPACITY & WEIGHTS

Inside Cubic Cap	acity 65.9 m³	2330 ft ³
Max Gross	32,500 kg	71,650 lbs
Payload	28,760 kg	63,400 lbs
Tare	3,740 kg	8,250 lbs

NOTE: The dimensions and door openings of all containers correspond to ISO standards. However, due to production tolerances, a difference in measurement is possible.

DISCLAIMER: Every effort is made to ensure this information is accurate, however Triton does not assume any liability for the accuracy of the information and content provided in marketing or information materials, or for the consequences resulting from using the information and content provided. Triton does not guarantee or claim that said information and content is exhaustive. Claims as to the exhaustive nature of said information and content are excluded. The information and content is only provided for advertising purposes and is non-binding. No explicit or implied warranties or guarantees are made. The container displayed only represents a sample of the entire fleet.



\circlearrowleft \hookrightarrow \mapsto



CLASSIFICATION

Lease

Available via Triton's global network of supply locations.


40ft High Cube **Open Top** Container




- · Corrugated steel panels with strong wooden floor to protect the cargo
- Designed for cargos that require special loading dimensions
- · Removable door header

- · Removable roof bows and durable tarpaulin with customs approved cable to cover the topside.
- · Two swingable doors with custom approved closures
- 11/8" thick marine wooden floors with center dividers

- · Several lashing rings and bars inside the container to secure the cargo
- · Triton's industry leading new production testing and inspection criteria ensures the highest quality container
- Backed up by Triton's global network of supply locations and dedicated leasing and support teams
- · Available in the high demand hub ports
- · Flexible lease terms to meet your company needs





EXTERNAL DIMENSIONS

Length	12,192 mm	40′ 0.0″
Width	2,438 mm	8′ 0.0″
Height	2,896 mm	9′ 6.0″

INTERNAL DIMENSIONS

Length	12,032 mm	39′ 5.7′
Width	2,352 mm	7′ 8.6′
Height	2,653 mm	8′ 8.4′

DOOR OPENING

Width	2,340 mm	7′ 8.1″
Height	2,585 mm	8′ 5.8″

CAPACITY & WEIGHTS

Max Gross	32,500 kg	71,650 lbs
Payload	28,590 kg	63,030 lbs
Tare	3,910 kg	8,620 lbs

NOTE: The dimensions and door openings of all containers correspond to ISO standards. However, due to production tolerances, a difference in measurement is possible.

DISCLAIMER: Every effort is made to ensure this information is accurate, however Triton does not assume any liability for the accuracy of the information and content provided in marketing or information materials, or for the consequences resulting from using the information and content provided. Triton does not guarantee or claim that said information and content is exhaustive. Claims as to the exhaustive nature of said information and content are excluded. The information and content is only provided for advertising purposes and is non-binding. No explicit or implied warranties or guarantees are made. The container displayed only represents a sample of the entire fleet.






Available via Triton's global network of supply locations.

20ft Used **Open Top** Container



- · Rugged corrugated steel exterior panels with a thick wooden floor
- Designed for cargos that require special loading dimensions
- · Removable roof bows and heavy duty tarpaulin
- Swivel-out door header
- 14 gauge corrugated steel sides and 14 gauge locking steel double-end swing doors
- 11/8" thick marine plywood floors, forklift tested to 16,000 lbs per 44 square inches
- · Tie down steel lashing rings, 4000 lbs. cap. each
- (2) way laden fork lift pockets

- Security roof tarpaulin locking cable
- Backed up by Triton's global network of supply locations and dedicated sales and support teams
- · Available globally





EXTERNAL DIMENSIONS

Length	6,058 mm	19′ 10.5″
Width	2,438 mm	8′ 0.0″
Height	2,591 mm	8′ 6.0″

INTERNAL DIMENSIONS

Length	5,895 mm	19′ 4.2′
Width (Between side panels)	2,352 mm	7′ 8.6′
Height	2,348 mm	7′ 8.4′

DOOR OPENING

Width	2,340 mm	7′ 8.1″
Height	2,280 mm	7′ 5.8″

CAPACITY & WEIGHTS

Inside Cubic	Capacity 32.5 m ^s	1,150 ft [*]
Max Gross	30,480 kg	67,200 lbs
Payload	27,780-28,320 kg	61,250-62,440 lbs
Tare	2,160-2,700 kg	4,760–5,950 lbs

NOTE: The dimensions and door openings of all containers correspond to ISO standards. However, due to production tolerances, a difference in measurement is possible.

DISCLAIMER: Every effort is made to ensure this information is accurate, however Triton does not assume any liability for the accuracy of the information and content provided in marketing or information materials, or for the consequences resulting from using the information and content provided. Triton does not guarantee or claim that said information and content is exhaustive. Claims as to the exhaustive nature of said information and content are excluded. The information and content is only provided for advertising purposes and is non-binding. No explicit or implied warranties or guarantees are made. The container displayed only represents a sample of the entire fleet.





Available via Triton's global network of supply locations.


40ft Used Open Top Container




- Rugged corrugated steel exterior panels with a thick wooden floor
- Designed for cargos that require special loading dimensions
- · Removable roof bows and heavy duty tarpaulin
- Swivel-out door header
- 14 gauge corrugated steel sides
- 14 gauge locking steel double end swing doors

- 11/8" thick marine plywood floors/omega-3 floors, forklift tested to 16,000 lbs per 44 square inches
- · Tie down steel lashing rings, 4000 lbs. cap. each
- (2) way laden fork lift pockets

- · Security roof tarpaulin locking cable
- Backed up by Triton's global network of supply locations and dedicated sales and support teams
- Available globally





EXTERNAL DIMENSIONS

Length	12,192 mm	40′ 0.0″
Width	2,438 mm	8′ 0.0″
Height	2,591 mm	8′ 6.0″

INTERNAL DIMENSIONS

Length	12,032 mm	39′ 5.7
Width	2,352 mm	7′ 8.6
Height	2,348 mm	7′ 8.4

DOOR OPENING

Width	2,340 mm	7′ 8.1″
Height	2,280 mm	7′ 5.8″

CAPACITY & WEIGHTS

Inside Cubic	Capacity	65.9 m³		2330 ft ³
Max Gross	30,480-3	2,500 kg	67,200-71	1,650 lbs
Payload	25,780-2	28,760 kg	56,840-63	3,400 lbs
Tare	3,700 kg-	-4,700 kg	8,160–10	,360 lbs

NOTE: The dimensions and door openings of all containers correspond to ISO standards. However, due to production tolerances, a difference in measurement is possible.

DISCLAIMER: Every effort is made to ensure this information is accurate, however Triton does not assume any liability for the accuracy of the information and content provided in marketing or information materials, or for the consequences resulting from using the information and content provided. Triton does not guarantee or claim that said information and content is exhaustive. Claims as to the exhaustive nature of said information and content are excluded. The information and content is only provided for advertising purposes and is non-binding. No explicit or implied warranties or guarantees are made. The container displayed only represents a sample of the entire fleet.







Lease

Available via Triton's global network of supply locations.

20ft Flush **Folding Flatracks**




- · Built to carry heavy or oversized cargoes
- · Great for specialized shipments of steel, pipes, drums and machinery
- Forklift pockets for easy empty handling

- Heavy duty steel frames and thick plank floors and lashing rings all around
- · With flush folding end frames to allow for efficient stacking and repositioning
- · Triton's industry leading new production testing and inspection criteria ensures the highest quality container
- · Available in the high demand hub ports

- Backed up by Triton's global network of supply locations and dedicated leasing and support teams
- Flexible lease terms to meet your company needs





EXTERNAL DIMENSIONS

Length (Base bottom casting)	6,058 mm	19′ 10.5′
Width (Base bottom casting)	2,438 mm	8′ 0.0′
Height (End frame up)	2,591 mm	8′ 6.0′
Height (End frame down)	370 mm	1′ 2.6′

INTERNAL DIMENSIONS

Length (Between end panels)	6,038 mm	19′ 9.7″
Width (Over bottom side rail)	2,194 mm	7′ 2.4″
Height (Side rail to top castings)	2,233 mm	7′ 3.9″

CAPACITY & WEIGHTS

Max Gross	45,000 kg	99,200 lbs
Payload	42,000 kg	92,590 lbs
Tare	3,000 kg	6,640 lbs

NOTE: The dimensions of containers correspond to ISO standards.

However, due to production tolerances, a difference in measurement is possible.

DISCLAIMER: Every effort is made to ensure this information is accurate, however Triton does not assume any liability for the accuracy of the information and content provided in marketing or information materials, or for the consequences resulting from using the information and content provided. Triton does not guarantee or claim that said information and content is exhaustive. Claims as to the exhaustive nature of said information and content are excluded. The information and content is only provided for advertising purposes and is non-binding. No explicit or implied warranties or guarantees are made. The container displayed only represents a sample of the entire fleet.





Lease

Available via Triton's global network of supply locations.

40ft Flush Folding Flatracks



- Built to carry heavy or oversized cargoes
- · Great for specialized shipments of steel, pipes, drums and machinery
- Forklift pockets for easy empty handling

- Heavy duty steel frames and thick plank floors and lashing rings all around
- · With flush folding end frames to allow for efficient stacking and repositioning
- · Triton's industry leading new production testing and inspection criteria ensures the highest quality container
- · Available in the high demand hub ports

- Backed up by Triton's global network of supply locations and dedicated leasing and support teams
- Flexible lease terms to meet your company needs





EXTERNAL DIMENSIONS

Length (Base bottom casting)	12,192 mm	40′ 0.0′
Width (Base bottom casting)	2,438 mm	8′ 0.0′
Height (End frame up)	2,591 mm	8′ 6.0′
Height (End frame down)	648 mm	2′ 1.5′

INTERNAL DIMENSIONS

Length (Between end panels)	12,182 mm	39′ 11.6′
Width (Over bottom side rail)	2,374 mm	7′ 9.5′
Height (Side rail to top castings)	1,959 mm	6′ 5.1′

CAPACITY & WEIGHTS

Max Gross	52,500 kg	115,740 lbs
Payload	47,260 kg	104,190 lbs
Tare	5,240 kg	11,550 lbs

NOTE: The dimensions of containers correspond to ISO standards.

However, due to production tolerances, a difference in measurement is possible.

DISCLAIMER: Every effort is made to ensure this information is accurate, however Triton does not assume any liability for the accuracy of the information and content provided in marketing or information materials, or for the consequences resulting from using the information and content provided. Triton does not guarantee or claim that said information and content is exhaustive. Claims as to the exhaustive nature of said information and content are excluded. The information and content is only provided for advertising purposes and is non-binding. No explicit or implied warranties or guarantees are made. The container displayed only represents a sample of the entire fleet.





Lease

Available via Triton's global network of supply locations.

40ft High Cube Flush Folding Flatracks




- Additional height provides extra capacity for your goods
- Built to carry heavy or out of gauge cargoes
- Heavy duty steel frames and thick plank floors

- · Great for specialized shipments of steel, pipes, drums and machinery
- With flush folding end frames to allow for efficient stacking

- Triton's industry leading new production testing and inspection criteria ensures the highest quality container
- Backed up by Triton's global network of supply locations and dedicated leasing and support teams
- Flexible lease terms to meet your company needs











FLATRACK FRONT

FLATRACK SIDE

FLATRACK REAR

EXTERNAL DIMENSIONS

Length (Base bottom casting)	12,192 mm	40′ 0.0″
Width (Base bottom casting)	2,438 mm	8′ 0.0″
Height (End frame up)	2,896 mm	9′ 6.0″
Height (End frame down)	648 mm	2′ 1.5"

INTERNAL DIMENSIONS

Length (Between end panels)	12,182 mm	39′ 11.6″
Width (Over bottom side rail)	2,374 mm	7′ 9.5″
Height (Side rail to top castings)	2,264 mm	7′ 5.1″

CAPACITY & WEIGHTS

Max Gross	52,500 kg	115,740 lbs
Payload	47,220 kg	104,100 lbs
Tare	5,280 kg	11,640 lbs

NOTE: The dimensions of containers correspond to ISO standards.

However, due to production tolerances, a difference in measurement is possible.

DISCLAIMER: Every effort is made to ensure this information is accurate, however Triton does not assume any liability for the accuracy of the information and content provided in marketing or information materials, or for the consequences resulting from using the information and content provided. Triton does not guarantee or claim that said information and content is exhaustive. Claims as to the exhaustive nature of said information and content are excluded. The information and content is only provided for advertising purposes and is non-binding. No explicit or implied warranties or guarantees are made. The container displayed only represents a sample of the entire fleet.





Lease

Available via Triton's global network of supply locations.

40ft Roll Trailer



- Available in 40ft length
- · Tonnage rating from 60 to 120 tons

- Payload is specifically designed for the movement of products such as high-value cargo such as yachts, rail carriages, steel and cables.
- · Triton's industry leading new production testing and inspection criteria ensures the highest quality unit.
- · Available globally.

- · Flexible lease terms to meet your company needs.
- Backed up by Triton's global network of supply locations and dedicated leasing and support teams.





EXTERNAL DIMENSIONS

Length	12,350 mm	40′ 6.2′
Width	2,500 mm	8′ 2.4′
Height	700 mm	2′ 3.6′
Over the wheel set	730 mm	2′ 4.7′
Ground clearance	218 mm	0′ 8.6′

CAPACITY & WEIGHTS

Capacity	100 tons
Tare	7.5 tons

DISCLAIMER: Every effort is made to ensure this information is accurate, however Triton does not assume any liability for the accuracy of the information and content provided in marketing or information materials, or for the consequences resulting from using the information and content provided. Triton does not guarantee or claim that said information and content is exhaustive. Claims as to the exhaustive nature of said information and content are excluded. The information and content is only provided for advertising purposes and is non-binding. No explicit or implied warranties or guarantees are made. The container displayed only represents a sample of the entire fleet.





Lease

Available via Triton's global network of supply locations.


62ft Roll Trailer



- · Available in 62ft length
- Supplied with or without 3 rails
- Designed to handle 2 track gauges: Standard Gauge (1,435mm track) and Three Foot Six Inch Gauge (1,067mm track)

- Tonnage rating from 90 to 100 tons
- · Payload is specifically designed for the movement of products such as rail-cars and over length cargo
- · Triton's industry leading new production testing and inspection criteria ensures the highest quality unit
- Backed up by Triton's global network of supply locations and dedicated leasing and support teams
- Available globally
- Flexible lease terms to meet your company needs





EXTERNAL DIMENSIONS

Length	19,290 mm	63′ 3.4″
Width	2,500 mm	8′ 2.4″
Height	800 mm	2′ 7.5″
Over the wheel set	850 mm	2′ 9.4″
Ground clearance	282 mm	11.1"

CAPACITY & WEIGHTS

Capacity (with 3 rails)	100 tons
Tare (with 3 rails)	12.9 tons

DISCLAIMER: Every effort is made to ensure this information is accurate, however Triton does not assume any liability for the accuracy of the information and content provided in marketing or information materials, or for the consequences resulting from using the information and content provided. Triton does not guarantee or claim that said information and content is exhaustive. Claims as to the exhaustive nature of said information and content are excluded. The information and content is only provided for advertising purposes and is non-binding. No explicit or implied warranties or guarantees are made. The container displayed only represents a sample of the entire fleet.

HERE. THERE. EVERYWHERE

We supply the world

Triton is the largest lessor of intermodal containers in the world with over 7 million TEU of containers. Our services are available in 89 countries around the globe. So, no matter where you need containers, we'll have them nearby. To find your nearest Triton Container Sales manager visit www.tritoncontainer.com.



Global inventory of cargoworthy containers for lease and sale.



Unrivaled container supply at competitive prices.



Outstanding and highly responsive customer services.



Global network of 20 offices and 3 independent agencies across 16 countries.



Equipment built to the highest quality.



Our size, strength and reliability make us the go-to supplier of intermodal shipping containers.



We're the biggest for a reason, contact our friendly experts and experience Triton's world-leading service and cost savings today. Imagine what we can do together.

www.tritoncontainer.com